

CLIPPER/DEFLECTION INDICATOR SYSTEMS

Matherne Instrumentation's deflection indicator system is designed to give accurate readings on small to medium drilling and workover rigs.

The system includes 12" deflection indicator mounted in a steel box, 10 dial set for use with different wire line sizes and lines strung, standard 25' hose, and deflection loadcell with c-clamp.

The system is portable, durable, and ready to be placed on the drill line instantly.

Metric equivalents in Kgs and DaN.

FEATURES:

- Ready for immediate use Each system is assembled, loaded with indicator fluid, calibrated, tested, and sealed before shipment.
- Adjustable dampers allow operator-controlled pointer sensitivity.
- Can be mounted near the driller or on the mast or derrick, for optimum setup in any drilling situation avoiding problems that can result from deadlinemounting, such as buffeting by line vibration.
- Equipped with 10 different dials calibrated for number and size of line in pounds, kilograms, or decanewtons, for easy, flexible measurement readings.
- Rugged, compact steel box with built-in handles makes it easy to transport

ADVANTAGES:

- Large, easy-to-read gauge
- Compatible with all industry-standard deadline anchors

ORDERING SPECIFICATIONS:

- Number of Lines strung
- Drilling line size
- Mast Capacity for Clipper Weight Indicator
- Length of Hose



Gauge and Steel Box with Deflection Loadcell and C-clamp