

POWER TONG SYSTEMS

Matherne Instrumentation's power tong system is designed to assure uniform and proper make-up of the string by indicating accurate torque applied to each joint when running pipe or casing.

The system can help reduce drill collar and tool joint failure resulting from improper make-up. The system includes 6" tong torque indicator with bracket, a standard 5 ft. hose, and a tension or compression load cell.

The convenient mounting design allows the gauge to be mounted in a driller's console, in a weight indicator box, locally on the power tong, or stand alone. The 6" dial face is available with combination dual scales for added versatility.

FEATURES:

- 6" dial face with colorful custom logos
- Standard capacities up to 120,000 ft/lbs
- Box mount or panel mount styles available
- Dual scales and metric equivalents in kg/m, N-m, DaN-m, and KPa-m are available
- Adjustable target pointer can be set to the desired capacity so the driller can work to a clear mark
- Loadcells available in tension or compression models to accommodate any tong design.



6" Power Tong Gauge Panel Mount

12500 10000 15000 15000 15000 15000 15000 17500 20000 2500 2500 2500 22500

6" Power Tong Gauge Box Mount

ADVANTAGES:

- Easily visible 6" dial face allows clear viewing from long distances
- Easily mounted in various locations: driller's console, weight indicator box, on the tong, or stand alone
- Fluid filled indicator reduces shock, vibration, and corrosion
- Adjustable damper allows for smooth pointer movement under intense situations
- The tension cylinder includes a fully machined stainless steel piston rod that gives added protection against harsh saltwater environments, ensuring a long service life and minimum maintenance.

ORDERING SPECIFICATIONS:

- Capacity of Indicator
- Length of Hose
- Style of Indicator
- Handle Length of Tong
- Type of Loadcell



Tension Load Cell



Compression Load Cell